

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Susanne KLEIN

Title: A DISPLAY

Appl. No.: Unassigned

Filing Date: 02/27/2002

Examiner: Unassigned

Art Unit: Unassigned



CLAIM FOR CONVENTION PRIORITY

Commissioner for Patents
Washington, D.C. 20231

Sir:

The benefit of the filing date of the following prior foreign application filed in the following foreign country is hereby requested, and the right of priority provided in 35 U.S.C. § 119 is hereby claimed.

In support of this claim, filed herewith is a certified copy of said original foreign application:

- ° Great Britain Patent Application No. 0105206.7 filed 03/02/2001.

Respectfully submitted,

Date February 27, 2002

FOLEY & LARDNER
Customer Number: 22428



22428

PATENT TRADEMARK OFFICE

Telephone: (202) 672-5485

Facsimile: (202) 672-5399

By

A handwritten signature in black ink, appearing to read "W. T. Ellis", written over a horizontal line.

William T. Ellis
Attorney for Applicant
Registration No. 26,874



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated: 31 May 2001



02MAR01 E610490-1 D01463
P01/7700.0.00-0105206.7

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference 30002178 GB

2. Patent application number
(The Patent Office will fill in this part)

0105206.7

02 MAR 2001

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Hewlett-Packard Company
3000 Hanover Street
Palo Alto
CA 94304, USA

Patents ADP number (If you know it)

Delaware, USA

If the applicant is a corporate body, give the country/state of its incorporation

496588001

4. Title of the invention A Display

5. Name of your agent (if you have one)

Richard A. Lawrence
Hewlett-Packard Ltd, IP Section
Filton Road
Stoke Gifford
Bristol BS34 8QZ

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Patents ADP number (If you know it)

7448038001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

12 ✓

Claim(s)

4 ✓

Abstract

1 ✓

Drawing(s)

2+2 ✓

10. If you are also filing any of the following, state how many against each item.

Priority documents

-

Translations of priority documents

-

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

1 ✓

Request for preliminary examination and search (Patents Form 9/77)

1 ✓

Request for substantive examination (Patents Form 10/77)

-

Any other documents (please specify)

Fee Sheet

11. I/We request the grant of a patent on the basis of this application.

Signature

Richard A. Lawrence

Date

1/3/01

12. Name and daytime telephone number of person to contact in the United Kingdom

Meg Joyce

Tel: 0117-312-9068

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

A Display

The present invention relates to display, in particular to a liquid crystal display illuminated by ambient light.

5

Some displays, such as liquid crystal displays, can be lit by a back light. The back light may need to be powerful, particularly if the optical efficiency of the display is low. Therefore, if the back light is part of a lap top
10 computer or other portable device, a heavy battery may be required to power the back light, which may be inconvenient.

Displays are known that operate without a back light by
15 reflecting ambient light, the reflectivity of the display being different at different points on the screen, so that reflected light forms an image. However, a substantial amount of ambient light incident on the display may be lost due to absorption within the display. Furthermore,
20 the user of the display may be tempted to point the display in the direction where the ambient light is strongest, which will lead to specular reflection of the ambient light off the display, thereby making the display less effective.

25

Another type of display which uses a planar waveguide to provide light through a liquid crystal layer is disclosed in a paper titled "Waveguide Based Liquid Crystal Display", by H. Yuan and P. Palffy-Muhoray, published in
30 Mol. Cryst. Liq. Cryst., 1999, Vol. 331, pp.281-288. This

uses total internal reflection between the liquid crystal and one planar substrate that bounds the liquid crystal, instead of birefringence between crossed polarizers. In this planar waveguide lit display, one or more light
5 sources must then be provided to couple light into the waveguide, for example at the periphery of a display. Light is then guided by the substrate and then deflected out of activated areas of the liquid crystal. This provides an efficient optical structure with a high
10 viewing angle. It may, however, be difficult to provide one or more light sources around the periphery of the display to illuminate the waveguide.

It is an object of the invention to provide a more
15 convenient display.

According to one aspect of the present invention, there is provided a display having a display area, and a light guide for providing light to the display area, the light
20 guide comprising:

a planar light guiding medium having a light emitting surface and one or more side faces disposed around the light emitting surface;
25

a plurality of light pipes, each light pipe having a collector end for collecting light and an output end, the output ends being arranged along the side faces so as to introduce the collected light into the guiding medium;
30

wherein the output ends of the light pipes are distributed along the or each side face.

5 The light pipes may then be distributed according to the amount of light needed across the display, or in a particular area of the display. In a preferred embodiment of the invention, the light pipes are distributed evenly along the or each side face.

10 The light guiding medium will channel light therealong but will allow some light to escape through the light emitting surface to illuminate the display area. It will be understood that the term planar light guiding medium will include a medium with some curvature, provided that the
15 curvature is sufficiently small that to allow the guiding medium to channel light therein.

Because the output ends of the light pipes are distributed evenly along the side faces of the light guiding medium,
20 light will be emitted from the light emitting surface more evenly. It will be appreciated that the light pipes outputs need not be distributed at the same intervals around all the side faces of the light guiding medium, and that if the light guiding medium is rectangular, the
25 intervals between light pipe outputs along the long sides may be different from the intervals along the short sides of the light guiding medium.

Preferably, the collector ends of the light pipes will be
30 distributed in a spaced apart fashion over a light

collecting area, the position of the collector ends on the light collecting area being scrambled relative to the position of the corresponding output ends on the side faces of the light guiding medium. Because of this, if a
5 portion of the light collecting area is obscured, the light emitted through the light emitting area will be diminished in a more uniform manner, and the likelihood of a shadow being formed in the display area will be reduced.

10 There may be some short range order between the positions of the output ends and the positions corresponding light collector ends. The light pipes may be grouped in pairs, the light output ends of each pair being adjacent to one another on a side face, and the collector ends of each
15 pair being adjacent to one another on the collecting area. However, a group of light pipes with neighbouring or nearby collector ends will preferably have output ends that are located on different portions of a side surface or, on different side surfaces.

20 The light guiding medium will preferably have a planar back surface, and a reflecting layer may be provided on the back surface of the light guiding medium, so as to increase the amount of light emitted through the light
25 emitting surface.

In a preferred embodiment, means are provided for applying an electrical signal to the guiding medium in one or more localised areas, and the guiding medium is responsive to
30 the electrical signal such that the optical properties of

the optical medium are changed in each localised area where the electrical signal is applied, with the result that in the localised areas where the electrical signal is applied, light travelling along the guiding medium exits
5 the guiding medium through the light emitting surface, and where the electrical signal is not applied, light within the light guiding medium is channelled therealong.

An image can be formed by applying the electrical signal
10 at the points where the desired image is light, the remaining area of the display appearing dark.

The electrical signal will preferably be in the form of a voltage applied across the guiding medium, but the
15 electrical signal may superposed on a background voltage level, such that the electrical signal at a point on the light guiding medium results in the absence of a voltage being applied at that point.

20 The guiding medium may have a refractive index whose value is changeable between a first value and a second value when an electrical signal is applied, the guiding medium having an index matching layer whose refractive index is close to the first value. In one embodiment, the
25 refractive index of the guiding medium will be more closely matched to the refractive index of the index matching layer at a point where an electrical signal is applied, and light will be emitted through the light emitting layer at that point. The light guiding medium
30 will preferably be liquid crystal material, since its

refractive index for at least one polarisation of light can easily be changed by applying an electric field.

5 So that the image produced by the screen can be viewed more easily by a person in front of the screen, a light scattering layer will preferably be provided between the light emitting surface and the light guiding layer.

10 Since the liquid crystal material will normally be birefringent, and since the refractive index for only one polarisation of light may be changed between a first value and a second value by the electrical signal, a quarter wave plate or other polarisation rotating element may be provided at each side face of the light guiding medium, in
15 order to increase the amount of light which can be affected by the change in refractive index of the liquid crystal material. A semi-reflecting mirror will preferably be provided on the outer surface of each quarter wave plate, so that light of one polarisation that is
20 internally incident on a side face will pass through a quarter wave plate a first time, will be reflected by the semi-reflecting mirror, and will then pass through the quarter wave plate a second time, emerging from the quarter wave plate with a second polarisation.

25

The collector ends of at least some of the light pipes may be secured together in a bunch having a collector face, and means may be provided for temporarily securing the bunch in an orientation relative to the display area. If
30 the ambient light from a particular direction is

particularly bright, a user will then be able to orient the bunch such that the connector ends face in the direction where the ambient light is bright, thereby increasing the brightness of the screen. Alternatively,
5 the end of the bunch may be optically coupled to an electrical light source.

In a preferred embodiment, the display will be secured in a casing, and the collector ends will be distributed over
10 at least a portion of the external surface of the casing. The display may be secured to the casing of a lap top computer, or other portable electronic device of the type having a display, such as a mobile telephone.

15 The light pipes will preferably be formed from optic fibres.

The invention will now be further described, by way of example, with reference to the following drawings in
20 which:

Figure 1 shows a plan view of a display having optic fibre with collector ends according to the invention;
25

Figure 2 shows a front view of a laptop computer with the display of Figure 1, where the collector ends are distributed over the external surface of the laptop casing;
30

Figure 3 shows a back view of the laptop computer of Figure 2;

5 Figure 4 shows a laptop computer with the display of Figure 1, where the optic fibres are secured together in a bundle;

10 Figure 5 shows a cross sectional view of the display in Figure 1 in one embodiment; and,

Figure 6 shows a cross sectional view of a portion of the display in Figure 1, in another embodiment.

15 In Figure 1, there is shown a display 10 having a display area 12 bounded by four sides 13a,13b,13c,13d. A plurality of optic fibres 14 are provided for guiding light towards the display area 12. Each fibre 14 has a collector end 18 through which light can enter the fibre 14 and a light output end 16 through which the collected light exits the
20 fibre 14.

25 In Figures 2 and 3, there is shown an electronic device, here a laptop computer 20 with the display 10 mounted in the casing 22 of the computer 20. The casing 22 has a plurality of apertures 24, in each of which there is mounted the collector end 18 of an optic fibre 14. Ambient light incident on the casing 20 of the computer is directed by the optic fibres 14 onto the display area 12 of the display 10.

30

The collector ends 18 of the fibres 14 are distributed on the casing 18 such that there is no relationship between the position of the output ends 16 and the position of the collector ends 18. Collector ends 18 which lie close together, for example within the dashed loop 26 in Figure 3, will have corresponding output ends 16 which are located on different sides of the display area 12. If the collector ends 18 within the dashed loop are obscured, for example by a nearby object or a human hand, the light exiting the display area 12 will be uniformly diminished, rather than a shadow being formed on the display area 12.

In an embodiment shown in Figure 4, at least some of the fibres 14 are bunched together in a semi-rigid cladding 64 extending from the casing 22. At one end of the cladding 64, the collector ends 18 form a bunch 70 having a collecting surface 72, the other end of the cladding 64 being secured to the casing 22. If the ambient light is strongest in one direction, the collecting surface 72 can be oriented in that direction in order to increase the amount of light provided to the display 12, and the semi-rigid cladding will support the collecting surface 72 in that orientation.

In Figure 5, there is shown, schematically, a cross sectional view through the display 10. The display 10 has a layer of liquid crystal (LC) material 30. A plurality of transparent upper address lines 42 and lower address lines 43 are respectively provided above and below the LC layer 30 in order to apply an electric field in at least one

localised area of the LC layer 30. An upper planarizing layer 46 is provided between the upper address lines 42 and the LC layer 30, and a lower planarizing layer 48 is provided between the LC layer 30 and the lower address lines 43. A layer of glass 50 is provided above the upper address lines 42, the outer surface 52 of the glass layer acting as a light emitting surface.

Where an electric field is not applied to the LC layer, light is channelled by the LC layer 30 such that is propagates along the layer 30 by undergoing multiple total internal reflections at the interfaces 54,56 between the LC layer 30 and the upper and lower planarizing layers 46,48 respectively. In a localised region 60 where an electric field is applied by a voltage across the address lines 42,43, the refractive index of the LC layer 30 is changed, such that total internal reflection no longer occurs at the upper boundary 54 and the lower boundary 56, and in that localised region 60, light exits the LC layer 30 and reaches the light emitting surface 52, thereby forming a bright region in the display area 12. A mirror 62 is provided below the lower address lines 43 so that light that leaves the LC layer through the lower boundary 56 is reflected back up, through the LC layer 30, and through the light emitting surface 52.

The glass layer 50 and/or the upper planarizing layer 46 will scatter the light passing therethrough, so that at least some of the light leaving the light emitting surface 52 leaves the surface in a normal or near normal

direction.

The LC layer 30 has a four side faces 15a.15b.15c.15d. against each of which there lies a quarter wave plate 44
5 followed by a semi-reflective mirror 47. The output end 16 of each fibre lies against a semi-reflective mirror, facing towards a side face of the LC layer 30. Light exiting the output end 16 of a fibre 14 first passes through the semi-reflecting mirror 47, and then through the
10 quarter wave plate 44, and into the LC layer 30.

Light that has travelled across the LC layer 30 will be reflected at least in part by a semi-reflective mirror 47, passing twice through the quarter wave plate 44 before
15 marking a further pass through the LC layer 30. The quarter wave plate 44 will rotate the polarisation of the light passing therethrough, in order to increase the amount of light emitted through the light emitting surface 52 if the refractive index of the LC layer 30 is only
20 changeable for one polarisation of light.

In another embodiment, shown schematically in Figure 6, the output end 16 of each fibre 14 passes through an aperture 66 in the quarter wave plate layer 44, such that
25 light entering the LC layer 30 from the optic fibre 14 does not pass through the quarter wave plate layer.

It will be appreciated from the above description that the present invention provides a simple and compact way of
30 collecting ambient light in order to illuminate a portable

- 12 -

display, thereby reducing the need for a battery powered light source.

Claims:

1. A display having a display area, and a light guide
for providing light to the display area, the light guide
5 comprising:

a planar light guiding medium having a light emitting
surface and one or more side faces disposed around the
light emitting surface;

10

a plurality of light pipes, each light pipe having a
collector end for collecting light and an output end, the
output ends being arranged along the side faces so as to
introduce the collected light into the guiding medium;

15

wherein the output ends of the light pipes are distributed
along the or each side face.

2. A display as claimed in Claim 1, wherein the
20 collector ends of the light pipes are distributed over a
light collecting area and wherein the position of the
collector ends on the light collecting area is scrambled
relative to the position of the corresponding output ends
on the side faces of the light guiding medium.

25

3. A display as claimed in Claim 2, wherein the display
is secured in a casing, and the collector ends are
distributed over at least a portion of the external
surface of the casing.

30

4. A display as claimed in any preceding claim, wherein the light guiding medium has a planar back surface, and wherein a reflecting layer is provided on the back surface of the light guiding medium.

5

5. A display as claimed in any preceding claim, wherein:

means are provided for applying an electrical signal to the guiding medium in one or more localised areas; and,

10

the guiding medium is responsive to the electrical signal such that the optical properties of the optical medium are changed in each localised area where the electrical signal is applied, with the result that

15

in the localised areas where the electrical signal is applied, light travelling along the guiding medium exits the guiding medium through the light emitting surface, and where the electrical signal is not applied, light within the light guiding medium is channelled therealong.

20

6. A display as claimed in Claim 5 wherein the guiding medium is a liquid crystal material.

25 7. A display as claimed in Claim 5 or Claim 6, wherein a scattering layer is provided between the light emitting surface and the light guiding layer.

8. A display as claimed in Claim 6 or Claim 7, wherein a
30 quarter wave plate is provide at the output of each light

pipe.

9. A display as claimed in any preceding claim, wherein the collector ends of at least some of the light pipes are
5 secured together in a bunch having a collector face, and means are provided for temporarily securing the bunch in an orientation relative to the display area.

10. A display as claimed in any previous claim, wherein
10 the light pipes are formed from optic fibres.

11. An electronic device comprising:

a casing, a display with a display area secured relative
15 to the casing, and a light guide for providing light to the display area, the light guide having:

a planar light guiding medium having a light emitting
surface and one or more side faces disposed around the
20 light emitting surface;

a plurality of light pipes, each light pipe having a
collector end for collecting light and an output end, the
output ends being arranged along the side faces so as to
25 introduce the collected light into the guiding medium;

wherein the output ends of the light pipes are distributed
evenly along the or each side face.

30 12. A light guide for providing light to a display area,

comprising:

a planar light guiding medium having a light emitting surface and one or more side faces disposed around the
5 light emitting surface;

a plurality of light pipes, each light pipe having a collector end for collecting light and an output end, the output ends being arranged along the side faces so as to
10 introduce the collected light into the guiding medium;

wherein the output ends of the light pipes are distributed evenly along the or each side face.

15 13. A display substantially as herein described with reference to or as shown in the accompanying drawings.

14. An electronic device substantially as herein described with reference to or as shown in the
20 accompanying drawings.

15. A light guide substantially as herein described with reference to or as shown in the accompanying drawings.

Abstract

A Display

5 The present invention relates to display, in particular to
a liquid crystal display illuminated by ambient light. The
display has a display area, and a light guide system for
providing light to the display area, the light guide
system comprising: a planar light guiding layer having a
10 light emitting surface and a plurality of side faces
disposed around the light emitting surface; a plurality of
light pipes, each light pipe having a collector end for
collecting ambient light and an output end, the output
ends being arranged along the side faces of the light
15 guiding layer so as to introduce the collected light into
the guiding medium. The output ends of the light pipes are
distributed evenly along each side face of the light
guiding layer so as to provide homogeneous illumination to
the display area.

20

Figure 2

1/2




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

FOLEY & LARDNER
3000 K Street, N.W., Suite 500
P. O. Box 25696
Washington, D.C. 20007-8696

SUSANNE Klein
84061-267